

University of Nebraska - Lincoln

DigitalCommons@University of Nebraska - Lincoln

Nebraska Tractor Tests

Tractor Test and Power Museum, The Lester F. Larsen


2008

Nebraska Summary: S682 New Holland T6020 Elite AS

Nebraska Tractor Test Laboratory

University of Nebraska-Lincoln, tractortestlab@unl.edu

Follow this and additional works at: <https://digitalcommons.unl.edu/tractormuseumlit>

 Part of the [Energy Systems Commons](#), [History of Science, Technology, and Medicine Commons](#), [Other Mechanical Engineering Commons](#), [Physical Sciences and Mathematics Commons](#), [Science and Mathematics Education Commons](#), and the [United States History Commons](#)

Laboratory, Nebraska Tractor Test, "Nebraska Summary: S682 New Holland T6020 Elite AS" (2008).
Nebraska Tractor Tests. 3183.

<https://digitalcommons.unl.edu/tractormuseumlit/3183>

This Article is brought to you for free and open access by the Tractor Test and Power Museum, The Lester F. Larsen at DigitalCommons@University of Nebraska - Lincoln. It has been accepted for inclusion in Nebraska Tractor Tests by an authorized administrator of DigitalCommons@University of Nebraska - Lincoln.

SUMMARY OF OECD TEST 2481-NEBRASKA SUMMARY 682

NEW HOLLAND T6020 ELITE AS DIESEL

16 SPEED

POWER TAKE-OFF PERFORMANCE

Power HP (kW)	Crank shaft speed rpm	Gal/hr (l/h)	lb/hp.hr (kg/kW.h)	Hp.hr/gal (kW.h/l)	Mean Atmospheric Conditions
MAXIMUM POWER AND FUEL CONSUMPTION					
Rated Engine Speed—(PTO speed—1037 rpm)					
99.0 (73.8)	2197	6.22 (23.54)	0.440 (0.268)	15.92 (3.14)	
Standard Power Take-off Speed (1001 rpm)					
100.2 (74.7)	2121	6.14 (23.26)	0.430 (0.261)	16.31 (3.21)	
Maximum Power - (1 hour)					
108.5 (80.9)	1901	6.15 (23.27)	0.398 (0.242)	17.65 (3.48)	

VARYING POWER AND FUEL CONSUMPTION

99.0 (73.8)	2197	6.22 (23.54)	0.440 (0.268)	15.92 (3.14)	Air temperature
86.4 (64.4)	2250	5.78 (21.88)	0.469 (0.285)	14.94 (2.94)	64°F (18°C)
65.6 (48.9)	2280	4.76 (18.00)	0.508 (0.309)	13.79 (2.72)	Relative humidity
44.1 (32.9)	2305	3.65 (13.82)	0.580 (0.353)	12.08 (2.38)	30%
22.3 (16.6)	2331	2.60 (9.83)	0.818 (0.498)	8.57 (1.69)	Barometer
--	2354	1.73 (6.55)	--	--	29.6" Hg (100.2 kPa)

Maximum Torque - 360.6 lb.-ft. (488.9 Nm) at 1399 rpm

Maximum Torque Rise - 52.3%

Torque rise at 1800 engine rpm - 32%

DRAWBAR PERFORMANCE (Unballasted - Front Drive Engaged) FUEL CONSUMPTION CHARACTERISTICS

Power Hp (kW)	Drawbar pull lbs (kN)	Speed mph (km/h)	Crank- shaft speed rpm	Slip %	Fuel Consumption lb/hp.hr (kg/kW.h)	Hp.hr/gal (kW.h/l)	Temp.°F (°C) cool- ing med	Air dry bulb	Barom. inch Hg (kPa)
Maximum Power—7th (7BLow) Gear									
78.7 (58.7)	5935 (26.4)	4.97 (8.00)	2199	2.5	0.548 (0.334)	12.78 (2.52)	190 (88)	77 (25)	28.8 (97.6)
75% of Pull at Maximum Power—7th (7BLow) Gear									
61.3 (45.7)	4445 (19.8)	5.17 (8.32)	2257	1.6	0.630 (0.383)	11.12 (2.19)	190 (88)	73 (23)	28.8 (97.6)
50% of Pull at Maximum Power—7th (7BLow) Gear									
41.4 (30.9)	2970 (13.2)	5.23 (8.42)	2290	0.9	0.728 (0.443)	9.63 (1.90)	190 (88)	73 (23)	28.8 (97.6)
75% of Pull at Reduced Engine Speed—8th (9CHigh) Gear									
61.3 (45.7)	4450 (19.8)	5.17 (8.32)	2022	1.7	0.550 (0.335)	12.74 (2.51)	189 (87)	79 (26)	28.8 (97.6)
50% of Pull at Reduced Engine Speed—8th (9CHigh) Gear									
41.4 (30.9)	2970 (13.2)	5.24 (8.42)	2035	0.9	0.633 (0.385)	11.07 (2.18)	189 (87)	77 (25)	28.8 (97.6)

Location of tests: Istituto per le Macchine Agricole
e Movimento Terra 73, Strada delle Cacce 10135
Torino Italy

Dates of tests: January to March, 2008.

Manufacturer: CNH Europe Holding S.A. 13, Rue
Aldringen L-1118 Luxembourg

FUEL and OIL: Fuel No. 2 Diesel **Specific gravity converted to 60°/60°F (15°/15°C)** 0.842
Fuel weight 7.01 lbs/gal (0.840 kg/l) **Oil SAE**
15W40 **API service classification** CH-4
Transmission and hydraulic lubricant Akcela
Nexplore fluid **Front axle lubricant** Akcela
Nexplore fluid

ENGINE: Make CNH Diesel **Type** four cylinder
vertical with turbocharger and air to air intercooler
Serial No. 444077 **Crankshaft** lengthwise **Rated engine speed** 2200 **Bore and stroke** 4.094" x
5.197" (104.0 mm x 132.0 mm) **Compression ratio**
16.5 to 1 **Displacement** 274 cu in (4485 ml) **Starting system** 12 volt **Lubrication** pressure **Air cleaner**
two paper elements and aspirator **Oil filter** one full
flow cartridge **Oil cooler** engine coolant heat
exchanger for crankcase oil, radiator for hydraulic
and transmission oil **Fuel filter** one paper element
Muffler underhood **Exhaust** vertical **Cooling medium temperature control** thermostat and
variable speed fan

CHASSIS: **Type** front wheel assist **Serial No.**
Z7BD02151 **Tread width** rear 60.0" (1524 mm) to
96.0" (2438 mm) front 52.2" (1325 mm) to 90.0"
(2285 mm) **Wheelbase** 95.0" (2412 mm) **Hydraulic control system** direct engine drive **Transmission**
selective gear fixed ratio with partial (8) range
operator controlled powershift **Nominal travel speeds mph (km/h)** first 1.41 (2.27) second 1.73
(2.78) third 2.10 (3.38) fourth 2.58 (4.15) fifth 3.31
(5.32) sixth 4.06 (6.53) seventh 4.94 (7.95) eighth
5.51 (8.86) ninth 6.06 (9.75) tenth 6.75 (10.87)
eleventh 8.23 (13.24) twelfth 10.09 (16.24)
thirteenth 12.94 (20.82) fourteenth 15.87 (25.54)
fifteenth 19.32 (31.09) sixteenth 23.70 (38.14)
reverse 1.39 (2.24), 1.71 (2.75), 2.08 (3.35), 2.55
(4.10), 3.27 (5.26), 4.01 (6.45), 4.88 (7.86), 5.44
(8.76), 5.99 (9.64), 6.67 (10.74), 8.13 (13.08), 9.97
(16.05), 12.78 (20.57), 15.68 (25.24), 19.10 (30.73),
23.43 (37.70) **Clutch** wet disc hydraulically actuated
by foot pedal **Brakes** wet disc hydraulically actuated
by two foot pedals that can be locked together
Steering hydrostatic **Power take-off** 540 rpm at
1970 engine rpm or 1000 rpm at 2120 engine rpm
Unladen tractor mass 11345 lb (5145 kg)

DRAWBAR PERFORMANCE

(Unballasted - Front Drive Engaged) MAXIMUM POWER IN SELECTED GEARS

Power Hp (kW)	Drawbar pull lbs (kN)	Speed mph (km/h)	Crank- shaft speed rpm	Slip %	Fuel Consumption lb/hp.hr (kg/kW.h)	Consumption Hp.hr/gal (kW.h/l)	Temp. °F(°C) cool- ing med	Air dry bulb	Barom. inch Hg (kPa)
68.9 (51.4)	11210 (49.9)	2.31 (3.71)	2224	15.2	4th(4ALow) Gear 0.617 (0.376)	11.36 (2.24)	190 (88)	73 (23)	29.0 (98.3)
79.7 (59.4)	9845 (43.8)	3.04 (4.89)	2160	9.3	5th(5BLow) Gear 0.545 (0.331)	12.87 (2.53)	190 (88)	73 (23)	29.0 (98.3)
86.8 (64.7)	8790 (39.1)	3.70 (5.96)	2067	5.7	6th(6BLow) Gear 0.499 (0.303)	14.06 (2.77)	189 (87)	73 (23)	29.0 (98.3)
90.3 (67.3)	7980 (35.5)	4.24 (6.82)	1896	3.7	7th(7BLow) Gear 0.476 (0.289)	14.73 (2.90)	187 (86)	68 (20)	29.0 (98.3)
92.4 (68.9)	7260 (32.3)	4.77 (7.67)	1900	3.3	8th(9CHigh) Gear 0.467 (0.284)	15.02 (2.96)	187 (86)	68 (20)	29.0 (98.3)
89.7 (66.9)	6345 (28.2)	5.30 (8.53)	1900	2.6	9th(8BLow) Gear 0.475 (0.289)	14.77 (2.91)	189 (87)	72 (22)	29.0 (98.3)
92.3 (68.8)	5865 (26.1)	5.90 (9.50)	1897	2.3	10th(10CHigh) Gear 0.471 (0.286)	14.88 (2.93)	187 (86)	75 (24)	29.0 (98.3)
88.4 (65.9)	4585 (20.4)	7.23 (11.64)	1901	1.6	11th(11CHigh) Gear 0.488 (0.297)	14.36 (2.83)	187 (86)	75 (24)	29.0 (98.3)
86.6 (64.6)	3625 (16.1)	8.96 (14.42)	1899	1.2	12th(12CHigh) Gear 0.499 (0.304)	14.05 (2.77)	187 (86)	70 (21)	29.0 (98.3)

NOTE : The data on this summary was obtained from OECD report 2444 conducted on the Case IH Maxxum 110 Pro Diesel.

REPAIRS AND ADJUSTMENTS: No repairs or adjustments

REMARKS: All test results were determined from observed data obtained in accordance with official OECD test procedures. This tractor did not meet the manufacturer's three point lift claim of 12185 lbs (5527 kg) nor cab sound level claim of 70.0 dB(A). The performance figures on this summary were taken from a test conducted under the OECD Code II test procedure.

We, the undersigned, certify that this is a true summary of data from OECD Report No. **2481**, Nebraska Summary 682, January 8, 2010.

Roger M. Hoy
Director

M.F. Kocher
V.I. Adamchuk
J.A. Smith
Board of Tractor Test Engineers

TRACTOR SOUND LEVEL WITH CAB	Front Wheel Drive	
	Disengaged dB(A)	Engaged dB(A)
At no load in 7th (7BLow) gear	69.8	70.1
Bystander	--	--

TIRES AND WEIGHT

Rear tires - No.,size, ply & psi(kPa)
Front tires - No.,size, ply & psi(kPa)
Height of Drawbar
Static Weight with operator- Rear
- Front
- Total

Tested Without Ballast

Two 600/65R38; **,12 (80)
Two 480/65R28; **,12 (80)
22.5 in (570 mm)
7055 lb (3200 kg)
4455 lb (2020 kg)
11510 lb (5220 kg)

This vehicle is equipped with an electronically controlled engine Power management system that monitors and boosts engine power output in certain circumstances. This is achieved by electronically changing the characteristics of the engine power-speed curve. The engine Power management function ("boosted" power level) becomes active in the higher transmission gears for road transport applications. The system is also activated when power transfer through the PTO exceeds a preset level (and forward speed exceeds 0.5 km/h), for mobile PTO driven implement applications. An override system is provided to enable PTO operations at the "boosted" power level while the vehicle is stationary for test purposes. The results of this PTO output test are presented below.

POWER TAKE-OFF PERFORMANCE

Power HP (kW)	Crank shaft speed rpm	Gal/hr (l/h)	lb/hp.hr (kg/kW.h)	Hp.hr/gal (kW.h/l)	Mean Atmospheric Conditions
MAXIMUM POWER AND FUEL CONSUMPTION					
Rated Engine Speed—(PTO speed—1037 rpm)					
117.5 (87.6)	2197	7.17 (27.14)	0.427 (0.260)	16.38 (3.23)	
Standard Power Take-off Speed (1000 rpm)					
122.4 (91.3)	2119	7.21 (27.31)	0.413 (0.251)	16.97 (3.34)	
Maximum Power - (1 hour)					
127.7 (95.2)	1899	7.22 (27.32)	0.396 (0.241)	17.69 (3.49)	
VARYING POWER AND FUEL CONSUMPTION					
117.5 (87.6)	2197	7.17 (27.14)	0.427 (0.260)	16.38 (3.23)	Air temperature
101.6 (75.8)	2236	6.38 (24.15)	0.440 (0.268)	15.93 (3.14)	65°F (19°C)
77.2 (57.6)	2263	5.33 (20.19)	0.484 (0.294)	14.48 (2.85)	Relative humidity
52.3 (39.0)	2297	4.16 (15.75)	0.557 (0.339)	12.59 (2.48)	35%
26.5 (19.8)	2325	2.79 (10.57)	0.738 (0.449)	9.50 (1.87)	Barometer
-- --	2354	1.74 (6.57)	-- --	-- --	29.6" Hg (100.4 kPa)
Maximum Torque - 377.0 lb.-ft. (511.1 Nm) at 1600 rpm					
Maximum Torque Rise - 34.2%					
Torque rise at 1800 engine rpm - 30%					

HYDRAULIC PERFORMANCE

CATEGORY: III

Quick Attach: None

OECD Static test

Maximum force exerted through whole range: 7735 lbs (34.4 kN)

i) Opening pressure of relief valve: NA

Sustained pressure of the open relief valve: 3005 psi (207 bar)

ii) Pump delivery rate at minimum pressure: 28.4 GPM (107.6 l/min)

iii) Pump delivery rate at maximum

hydraulic power: 24.8 GPM (93.9 l/min)

Delivery pressure: 2755 psi (190 bar)

Power: 39.8 HP (29.7 kW)

THREE POINT HITCH PERFORMANCE

Observed Maximum Pressure psi.(bar)

3005 (207)

Location:

lift cylinder

Hydraulic oil temperature: °F (°C)

150 (66)

Location:

hydraulic sump

Category:

III

Quick attach:

None

SAE Static Test—System pressure 2715 psi (187 Bar)

Hitch point distance to ground level in. (mm)	7.9 (200)	15.7 (400)	23.0 (585)	31.5 (800)	39.4 (1000)
Lift force on frame lb	14655	13375	13060	12520	11355
" " " " " " (kN)	(65.2)	(59.5)	(58.1)	(55.7)	(50.5)

HITCH DIMENSIONS AS TESTED—NO LOAD

	OECD test		SAE test	
	inch	mm	inch	mm
A	30.3	770	31.0	788
B	12.2	310	12.2	310
C	15.6	395	15.6	395
D	14.6	370	14.6	370
E	7.9	200	9.8	250
F	9.3	235	9.3	235
G	32.3	820	32.3	820
H	1.2	30	1.2	30
I	16.9	430	15.6	395
J	23.0	585	23.0	585
K	19.9	505	23.0	585
L	46.4	1178	46.4	1178
M	24.5	623	24.5	623
N	39.8	1010	39.8	1010
O	7.9	200	7.9	200
P	50.0	1270	45.0	1144
Q	36.8	935	34.3	872
R	32.3	820	34.1	867

